>POWER

Engine	3-cylinder, inline 4-stroke, liquid-cooled, DOHC
Displacement	675cc
Bore x Stroke	72×55.2 mm
Maximum Power	66kW/11,000rpm
Maximum Torque	68Nm/8,250rpm
Fuel System	BOSCH EFI
Compression Ratio	11.5:1
Transmission	CF-SC slipper assist clutch, 6-speed, wet, multi-plate
Throttle	Mechanical throttle
Top Speed	>220km/h
Emission	Euro V+

>CHASSIS/SUSPENSION/BRAKES

Frame	Steel tubular frame
Swingarm	Aluminum alloy high-arch twin swingarm
Rim	Aluminum alloy
Front Tire	120/70 R17 (CST S3N)
Rear Tire	180/55 R17 (CST S3N)
Front Suspension	Ø41 inverted suspension, fully adjusatble, KYB
Rear Suspension	Monoshock rear suspention, adjustable preload & rebound, KYB
Front/Rear Suspension Travel	130mm/130 mm
Front Brake	300mm twin discs, four-piston radial caliper, J.Juan
Rear Brake	240mm single disc, single-piston sliding caliper
ABS	Standard
Traction Control	Standard, two-level adjustable, switchable

>DIMENSIONS & WEIGHT

LxWxH	2,020x728x1,105mm
Steering Angle	36°
Rake	23.7°
Trail	93.2mm
Wheelbase	1400mm
Seat Height	810mm (830/795mm with accessory seats)
Ground Clearance	140mm
Fuel Tank Capacity	15L
Dry Weight	175kg

>ELECTRONICS

Dash	5-inch TFT dislplay
Battery	12V
Day-Running-Light	LED
Key	Mechanical key
Quickshifter	Upshifting
Tire Pressure Monitor	Accessory
Headlight	LED animated
Taillight	LED
Signal Light	LED
USB Charge Portal	USB type-A & type-C
Action Camera Control	Accessory
Steering Stabilizer	Accessory
Heated Grips	Accessory
OTA Upgrade	Standard
APP Connectivity	Standard
T-BOX	Optional

CFMOTO

675SR-R

RACING TRIPLE



ZHEJIANG CFMOTO POWER CO., LTD.

No. 116, Wuzhou Road, Yuhang Economic Development Zone Hangzhou 311100, Zhejiang Province.

www.cfmoto.com/global
@CFMOTOOFFICIAL
@cfmotooffical
CFMOTO
CFMOTO
@cfmoto_official

675SR-R

RACING TRIPLE

DYNAMIC DESIGN

-Aerodynamic bodywork: winglets and brake's air inlets
-Signature led animated lights
-High-arch aluminum swingarm
-Transbody line design element

TRIPLE-CYLINDER ENGINE

-Sporty exhaust sound
-Low vibrations at high rpm

SPORT-ORIENTED CHASSIS

-Alloy steel tubular frame
-Front suspension: ø 41mm USD fully adjustable KYB
rear suspension: monoshock with adjustable preload & rebound KYB
-Front brakes: 300 mm discs, 4-piston calipers,radial brake pump J. Juan
rear brakes: 240 mm disc, single-piston caliper

TIME-ATTACK FEATURES

-Quick-shifter,for fast upshifting
-Lap time chrono
-Traction control: 2 levels
-CST S3N dual compound sport tires

ADVANCED ELECTRONICS

-5" TFT display
-Supports various smart features such as My Ride, Real-time location, Reminders, etc.
with CFMOTO RIDE APP
(*The vehicle must be equipped with a T-Box device to enable the above features.)

RACE-INSPIRED RIDING POSITION

-15L ergonomic fuel tank
-Tail hump cover with action camera adaptor (Accessory)
-Seat height 810 mm
(830 / 795 mm with accessory seats)





Aerolite Grey



Nebula Black



Nebula White